

# tactile $\mu$ Console



A new generation of miniaturized tactile LCD micro console for the programming and the teleloading of the new range of ARDETEM signal conditioners.

It allows:

- The visualization of the measure and the status of the analog, relay and digital outputs.
- The visualization and the modification of the programming.
- The teleloading of programming files for duplication to other signal conditioners.

## Description



The graphical tactile rear-lit LCD allows the visualization of the following information:

- The value of the measure with its unit
- The product tag name
- The value(s) of the analog output(s)
- The status of the relay outputs and the RS485 communication
- Scrolling message for programming help in various languages
- Two keys with programmable functions (Min, Max, clear, setting of the setpoints...)

## Features

- Dimensions (HxLxD): 90 x 22.6 x 24
- Material: self-extinguishing black UL 94VO PA66
- IP 40 housing
- CE marking

ARDETEM - CA CO/154 - A 04/16 - Any data in this documentation may be modified without prior notice.

**ARDETEM**<sup>®</sup>

e-mail : [info@ardetem.com](mailto:info@ardetem.com)  
[http : //www.ardetem.com](http://www.ardetem.com)

Route de Brindas  
Parc d'activité d'Arbora N°2  
69510 SOUCIEU EN JARREST  
FRANCE

Tél. : 33 (0)4 72 31 31 30  
Fax. : 33 (0)4 72 31 31 31

your representative

